



Forever Medical

-86 Degree Deep Freezer

The -86 °C deep freezer can control the temperature inside from -40 degree to -86 degree, and set two silicone rubber seals for the out door to keep the better thermal effect and energy saving. Italy computer control system, Germany or Italy compressor used, EMB fan, etc to make sure the better freezing quality for the freezer.



Upright Style

Prices Temperature controlling :

Using Italy micro computer control system, high accuracy sensor to control, display, and warning;

Inner temperature range in -40 to -86°C, digital display.

Microprocessor-based temperature control system.

Safety Functions :

Warning system for high and low temperature, sensor failure, etc;

Warning mode with buzzer, light flashing;

Time-delay prevention when starting up in case of overload current rushing.

Cooling system :

Full sealed Germany or Italy branded compressor, CFC free high efficiency refrigerant;

Using EMB fan and high efficient evaporator and condensation, quickly freezing and low energy consume;

Excellent cooling system design, freezing quickly, saving energy style;

Thickness foaming layer, CFC free thermal material used to keep better thermal effect than regularly;

New and environment friendly raw material used.

Tel: +86-15736746522

Web: www.yongjiumed.com

Add: Room 806, Floor 8, Wanda Center, Jinshui District, Zhengzhou, Henan, China

Fax: 0371-61340851

Email: judyd@yjcompany.com

Postcode: 450000

Humanized design :

Solid door designing,with safety lock and key,better thermal effect ;

Automatic rebound iron hinges designing;

Whole stainless steel inner wall and shelves;

LED digital display,convenient to watch;

Frost free design,easy to defrost and clean;

Inner LED lighting design;

Wide range of voltage design,range from 187~242 volts,50HZ/60HZ(Optional).

Optional:Temperature recorder,professional large door handle for outer door opening easily.

Main Technical Parameters:

Model	Capacity	Temp	External Size W*D*H/mm	Voltage (V/HZ)	Power	Climate	N.W.	Shelve
YJ-86-30-LA	30L	-40 ~ -86 °C	470*490*1120	220/50	350	N	60	1
YJ-86-60-LA	60L	-40 ~ -86 °C	540*620*1115	220/50	450	N	75	1
YJ-86-80-LA	80L	-40 ~ -86 °C	620*660*1275	220/50	480	N	90	1
YJ-86-158-LA	158	-40 ~ -86 °C	620*660*1795	220/50	500	N	115	2
YJ-86-328-LA	328	-40 ~ -86 °C	760*765*1975	220/50	550	N		3
YJ-86-400-LA	400	-40 ~ -86 °C	760*865*1975	220/50	750	N	230	3
YJ-86-550-LA	550	-40 ~ -86 °C	860*965*1975	220/50	750	N		3
YJ-86-600-LA	600	-40 ~ -86 °C	940*950*1920	220/50	1200	N	280	3
YJ-86-638-LA	638	-40 ~ -86 °C	960*965*1975	220/50	1300	W		3
YJ-86-750-LA	750	-40 ~ -86 °C	1060*965*1975	220/50	1400	N		3
YJ-86-940-LA	940	-40 ~ -86 °C	1240*1000*2000	220/50	1700	N	320	3

Tel: +86-15736746522

Web: www.yongjiumed.com

Add: Room 806,Floor 8,Wanda Center,Jinshui District,Zhengzhou,Henan,China

Fax: 0371-61340851

Email: judyd@yjcompany.com

Postcode:450000